



BEAM CLAMPS



Product Data Sheet



C - Beam Clamp



Top & Wide Beam Clamp

Description

Beam Clamps are designed to attach mechanically to the bottom flange of a steel beam.

Standard Construction

Malleable Iron with Hardened Steel Cup Point
Set Screw
Electro Zinc Plated
Do not overtighten the bolt, as this could exceed max load

Top Beam Clamp								
ROD SIZE(in)	MAX LOAD (LB)	MAX PIPE (in)	B (in)	C (in)	D (in)	E (in)	F (in)	WEIGHT (lb)
3/8	400	4	1-5/8	1-1/2	1	3/4	1/2	0.33
1/2	500	8	1-11/16	1-1/2	1-1/16	3/4	1/2	0.34
Wide Beam Clamp								
ROD SIZE(in)	MAX LOAD (LB)	MAX PIPE (in)	B (in)	C (in)	D (in)	E (in)	F (in)	WEIGHT (lb)
3/8	400	4	1-5/8	1-7/8	1-1/16	1-1/4	1/2	0.37
1/2	500	4	1-5/8	1-7/8	1-1/16	1-1/4	1/2	0.35
C - Clamp								
ROD SIZE(in)	MAX LOAD (lb)	PIPE SIZE (in)	C (in)	D (in)	E (in)	F (in)	WEIGHT (lb)	
3/8	400	1/2 to 2	1-3/4	1-3/4	5/8	3/4	0.33	
1/2	400	2-1/2 to 3-1/2	1-3/4	5/8	3/4	3/4	0.9	

Packaging

Size	Qty Per Box
3/8"	100
1/2"	100
#38T - 3/8" malleable clamp	100
#12T - 1/2" malleable clamp	100
#38W-3/8"wide malleable clamp	100
#12W-1/2"wide malleable clamp	100

Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

Elgen Manufacturing

10 Railroad Ave, Closter NJ 07624
Tel: 800.503.9805 :: Fax: 201.964.9030
info@elgenmfg.com :: www.elgenmfg.com