


SPRING NUTS



Product Data Sheet



Features

The nuts are made with "teeth" in the parallel channel recesses and made to grip in the strut channel.

The "teeth" promises positive locking strut channels to the fittings.

Description

Used to attaching or connecting 1-5/8 strut channel.

Optional Construction

Stainless Steel 304
Aluminum

Standard Construction

Made from low-carbon steel with Electrogalvanized finish.

Packaging

Thread Size(in) (A)	Width(in) (C)	Height(in) (E)
1/4-20	1-3/8	1/4
3/8-16	1-3/8	3/8
1/2-13	1-3/8	1/2

Size (in)	Qty Per Box
1/4	100
3/8	100
1/2	100

Thread Size(in)	Gauge	Allowable Pull-out Strength		Resistance to Slip		Torque	
		Lbs	kN	Lbs	kN	ft Lbs	Nm
1/4-20	12	2000	8.9	1500	6.7	50	70
3/8-16	12	100	4.4	800	3.6	19	25
1/2-13	12	600	2.7	300	1.3	6	8
1/4-20	14	1400	6.2	100	4.4	50	70
3/8-16	14	1000	4.4	750	3.3	19	25
1/4-20	14	600	2.7	300	1.3	6	8

Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

Elgen Manufacturing

10 Railroad Ave, Closter NJ 07624
Tel: 800.503.9805 :: Fax: 201.964.9030
info@elgenmfg.com :: www.elgenmfg.com